


News Letter_July.2018_Item of the month

Item of the month 



200W,150W,100W How to install



LED Flood lighting 100W



Public procurement NO:23327113
Big space lighting 100W
100% waterproof, dimmable, dimmer proof, dust proof
at proof floodlight fully supported in the space
below, sports and leisure lighting

CE FC RoHS

STANDARD 100W ultra proof IP65 certified, sealed cabinet and 60-70% savings electricity cost					
Total flux	Luminance efficiency	Beam angle	CR	CCT	
10,200lm	105lm/W	20° / 20° / 60° / 70°	Over 80	5700K 2000K-3000K	
Converter	Input voltage	Power consumption	PF	Converter efficiency	
UL listed UL904	AC100V-250V 50/60Hz	100W	Over 0.95	90%	
IP level	IK level	Weight	Working temperature	Heat sink material	Cover material
IP67	IK10	Lighting 3.5kg Converter 2.8kg	-40~90°C	AL 6063	PMMA Carbonate

LED Flood lighting 150W



Public procurement NO:23327114
Big space lighting 150W
100% waterproof, dimmable, dimmer proof, dust proof
at proof floodlight fully supported in the space
below, sports and leisure lighting

CE FC RoHS

STANDARD 150W ultra proof IP65 certified, sealed cabinet and 60-70% savings electricity cost					
Total flux	Luminance efficiency	Beam angle	CR	CCT	
15,450lm	105lm/W	20° / 20° / 60° / 70°	Over 80	5700K 2000K-3000K	
Converter	Input voltage	Power consumption	PF	Converter efficiency	
UL listed UL904	AC100V-250V 50/60Hz	150W	Over 0.95	90%	
IP level	IK level	Weight	Working temperature	Heat sink material	Cover material
IP67	IK10	Lighting 3.5kg Converter 2.8kg	-40~90°C	AL 6063	PMMA Carbonate

LED Flood lighting 200W



Public procurement NO:23327115
Big space lighting 200W
100% waterproof, dimmable, dimmer proof, dust proof
at proof floodlight fully supported in the space
below, sports and leisure lighting

CE FC RoHS

STANDARD 200W ultra proof IP65 certified, sealed cabinet and 60-70% savings electricity cost					
Total flux	Luminance efficiency	Beam angle	CR	CCT	
19,800lm	105lm/W	20° / 20° / 60° / 70°	Over 80	5700K 2000K-3000K	
Converter	Input voltage	Power consumption	PF	Converter efficiency	
UL listed UL904	AC100V-250V 50/60Hz	200W	Over 0.95	90%	
IP level	IK level	Weight	Working temperature	Heat sink material	Cover material
IP67	IK10	Lighting 3.5kg Converter 2.8kg	-40~90°C	AL 6063	PMMA Carbonate



1 Company No. 01, Sun H, Gyeonggi-do, Korea
Tel: +82-31-820-0111
Fax: +82-31-820-0112
www.stellon.net
E-mail: stellon@stellon.net
24 hr. 24 hr. 24 hr.

