

## News Letter\_May.2019\_Monthly News letter

EGM Tech News



Recently, EGM TECH exported 150 samples, including factories, to The factory in Indonesia for sample installation.

In particular, Indonesia was very difficult to export because of the strict regulations on customs. However, the success of the company has made it possible to increase its overseas export capacity.

As the supply of domestic lighting market becomes more difficult, Vietnam is exporting not only to Indonesia but also Japan, the Middle East and Southeast Asia based on the introduction of the branch office in Vietnam.



On April 17, the President of Indonesia, who is sure to be president, is touring the candidates shortly after he decides to relocate the capital.

Presently, before the presidential election, many presidents have promoted the relocation of the capital but the relocation has not occurred.

The presidential election is expected to take up 60 percent of the parliamentary seats in the ruling coalition party, and it is expected that the transfer of capital will be approved by the National Assembly.

He said that he has traveled to the eastern part of Indonesia by reason of balanced national development and considered it as a convenient capital destination for transportation with major cities.



If the capital is transferred in this way the balance of development will become more active and the regional economy will be revitalized and the construction business will be actively promoted and the surge of the indirect high-rise buildings of the capital Jakarta will be relieved.



Lighting for construction work

LED 170W cylindrical lighting suitable for indoor construction work lighting

■ Product Features

01. Indoor work lighting

02. Connectable

03. Portability

04. Able to separate

■ Specifications

LED	170W	Material	Aluminum	Color	White	OCCT	IP65
Beam angle	120°	Beam angle	120°	Beam angle	120°	Beam angle	120°
Power	170W	Power	170W	Power	170W	Power	170W
Input voltage	AC 100-240V	Input voltage	AC 100-240V	Input voltage	AC 100-240V	Input voltage	AC 100-240V
Output voltage	AC 100-240V	Output voltage	AC 100-240V	Output voltage	AC 100-240V	Output voltage	AC 100-240V
Beam diameter	170mm	Beam diameter	170mm	Beam diameter	170mm	Beam diameter	170mm
Beam length	2100mm	Beam length	2100mm	Beam length	2100mm	Beam length	2100mm
Material	Aluminum	Material	Aluminum	Material	Aluminum	Material	Aluminum
Weight	17kg	Weight	17kg	Weight	17kg	Weight	17kg

■ Product dimensions (1700mmx450mmx210mm)



