



News Letter_Feb.2020_Monthly News letter

Egm item news



In December 2019, an unknown cause of pneumonia occurred in Wuhan, Hubei, China.

Wuhan City's outbreak of pneumonia was reported when the Wuhan City Health and Welfare Commission announced on December 31, 2019 that 27 unexplained pneumonia patients were in quarantine.



Coronavirus infections originated in China have spread from all over the world, including Korea to patients in Thailand, Japan, Singapore, Taiwan and Vietnam, followed by the US, Canada France and Germany.



As of February 10, 2020, there were more than 40,000 confirmed global deaths and more than 900 deaths, with most deaths occurring in China but one death in Hong Kong and the Philippines outside of China.



LED Flood lighting 80W

Public procurement NO: 23327115
Longbody narrow 80W
100% waterproof, dimmable, dual zone of beam, adjustable, adjustable, in big space lighting, sports and culture lighting.

STANDARD Product wide power LED surface, recessed panel and 10-175 degree electric cord

Total flux	Beam angle	CR	CCT
17,700lm	120°/180°	Over 80	5000K
IP level	Weight	Beam	Year release
IP67	2.1 Kg	80W	AC220V (100V-240V)

CE, FCC, RoHS, etc.

LED Flood lighting 100W

Public procurement NO: 23327115
Big space lighting 100W
100% waterproof, dimmable, dual zone of beam, adjustable, adjustable, in big space lighting, sports and culture lighting.

STANDARD Product wide power LED surface, recessed panel and 10-175 degree electric cord

Total flux	Beam angle	CR	CCT
18,000lm	120°/180°	Over 80	5000K
Converter	Input	Output	IP
AC220V-240V	100W	Over 80W	IP67
Dimm	Beam	Over 80	RoHS
IP level	Weight	Beam	Year release
IP68	1.7kg	100W	AC220V (100V-240V)

CE, FCC, RoHS, etc.



LED Flood lighting 150W

Public procurement NO: 23327114
Big space lighting 150W
100% waterproof, dimmable, dual zone of beam, adjustable, adjustable, in big space lighting, sports and culture lighting.

STANDARD Product wide power LED surface, recessed panel and 10-175 degree electric cord

Total flux	Beam angle	CR	CCT
15,400lm	120°/180°	Over 80	5000K
Converter	Input	Output	IP
AC220V-240V	150W	Over 80W	IP67
Dimm	Beam	Over 80	RoHS
IP level	Weight	Beam	Year release
IP68	1.7kg	150W	AC220V (100V-240V)

CE, FCC, RoHS, etc.



