


News Letter_Feb.2020_Monthly News letter



In December 2019, an unknown cause of pneumonia occurred in Wuhan, Hubei, China.

Wuhan City's outbreak of pneumonia was reported when the Wuhan City Health and Welfare Commission announced on December 31, 2019 that 27 unexplained pneumonia patients were in quarantine.



Coronavirus infections originated in China have spread from all over the world, including Korea to patients in Thailand, Japan, Singapore, Taiwan and Vietnam, followed by the US, Canada France and Germany.



As of February 10, 2020, there were more than 40,000 confirmed global deaths and more than 900 deaths, with most deaths occurring in China but one death in Hong Kong and the Philippines outside of China.



LED Flood lighting 80W

Public procurement NO:23327115
Longbody noxious 80W

100% waterproof, durable, dust proof
all parts finished with superior, 5-year warranty
RoHS, REACH and other safety

STANDARD Product water proof IP67 vertical, silver painted and 50-70% savings electricity cost	
Total flux	8000lm/h
Beam angle	CR1
CR2	CCCT
1770lm/h	2.27m/h
100lm/h	1.1m/h
Weight	1.1kg
Dimensions	100x100x100
Power	80W
Input voltage	AC220V
IP67	2.1 Kg
Operating	-40~50°C
Beam	CR1
CR2	CCCT
1770lm/h	2.27m/h
100lm/h	1.1m/h

LED Flood lighting 100W

Public procurement NO:23327115
Big space lighting 100W

100% waterproof, durable, dust proof
all parts finished with superior, 5-year warranty
RoHS, REACH and other safety

STANDARD Product water proof IP67 vertical, silver painted and 50-70% savings electricity cost	
Total flux	10000lm/h
Beam angle	CR1
CR2	CCCT
2200lm/h	2.27m/h
100lm/h	1.1m/h
Weight	1.1kg
Dimensions	100x100x100
Power	100W
Input voltage	AC220V
IP67	2.1 Kg
Operating	-40~50°C
Beam	CR1
CR2	CCCT
2200lm/h	2.27m/h
100lm/h	1.1m/h



LED Flood lighting 150W

Public procurement NO:23327114
Big space lighting 150W

100% waterproof, durable, dust proof
all parts finished with superior, 5-year warranty
RoHS, REACH and other safety

STANDARD Product water proof IP67 vertical, silver painted and 50-70% savings electricity cost	
Total flux	15000lm/h
Beam angle	CR1
CR2	CCCT
3300lm/h	2.27m/h
100lm/h	1.1m/h
Weight	1.1kg
Dimensions	100x100x100
Power	150W
Input voltage	AC220V
IP67	2.1 Kg
Operating	-40~50°C
Beam	CR1
CR2	CCCT
3300lm/h	2.27m/h
100lm/h	1.1m/h



